



A. STAINLESS THIMBLE

Size indicates wire or rope diameter. Each.

21-0480	1/16"-3/32"	\$.85
21-0484	5/32"-3/16"	\$ 1.60
01-0034	3/32"-1/8"	\$ 1.50
01-0036	5/32"-3/16"	\$ 1.60
21-0486	1/4"	\$ 3.60

B. NICROPRESS OVAL

Locks wire rope to a thimble terminal. Close with an appropriate swaging tool for maximum strength. Each.

02-1020	1/16"	\$.25
02-1030	3/32"	\$.50
02-1040	1/8"	\$ 1.10
02-1050	5/32"	\$ 1.40

C. STANDARD STOP SLEEVE

Grips a single wire to provide a "stop" for halyard hooks or trapeze handle, etc. A special "J" size opening on a nicropress tool is required for closing.

02-1031	3/32"	\$.50
02-1041	1/8"	\$.65
02-1051	5/32"	\$ 1.00
02-1061	3/16"	\$ 1.10



Note: Special machinery is required for installation of these fittings.

H. MARINE EYES

Stainless.

02-1034	3/32"	\$ 7.50
02-1044	1/8"	\$ 9.25
02-1054	5/32"	\$ 11.25

I. MARINE FORKS

Stainless.

02-1035	3/32"	\$ 9.00
02-1045	1/8"	\$ 13.50
02-1055	5/32"	\$ 15.50

J-L. MARINE TURNBUCKLES & REPLACEMENT STUDS

Stainless. All are by C. Sherman Johnson except #02-1046.

J. 02-1048	1/8" Turnbuckle	\$ 33.00
02-1048-2	Turnbuckle Body Tubular	\$ 19.50
02-1058	5/32" Turnbuckle	\$ 35.50
K. 02-1049	1/8" Calibrated Stay Adjuster	\$ 35.00

02-1046	1/8" Stud Right Hand	\$ 18.00
L. 02-1047	1/8" Stud Left Hand	\$ 18.00
02-1057	5/32" Stud Left Hand	\$ 19.00
02-1056	5/32" Wire-5/16" Stud & Nut (H-20 forestry upgrade)	\$ 19.00
02-1056-1	Nut Only for #02-1056	\$ 2.00



D. MAIN HALYARD HOOK

For H-14/16s, Prindles and Sol Cats and for Nacras that use the wire main halyard. 25-3330 \$ 9.00

E-F. STAINLESS "S" HOOKS

Welded hooks. #56-9650 is for all Nacras. #56-9839 is for Prindle-style jib halyards. E. 56-9650 \$ 45.00
F. 56-9839 \$ 10.00



G-H. RINGS

G. 25-3050	2" Stainless (Prindle-Style Jib Halyards)	\$ 5.00
22-3320	1/8" x 3/4" ID Stainless	\$ 2.25
22-3525	3/16" x 3/4" ID Stainless	\$ 2.75
25-3904	1/4" x 2" OD "D" Stainless	\$ 5.00
H. 27-190570	3/8" x 2" ID Nylon	\$ 1.60

STA/MASTER TURNBUCKLE

Shorten your diamond wires and use an adjuster. The Sta/Master's finely calibrated center traveler quickly locks for exact repeatable settings for each condition. No need to swage. Stainless steel. Minimum length is 4" with 2-5/8" range. Max. load 1/8" cable.

02-1043 \$ 39.95



#2 SWAGE-IT RIGGING KIT

Have everything there when you need it! For rigging and emergency repairs. Includes swage-it tool, cutter, extension wrench, and 1/16", 3/32" and 1/8" oval sleeves. Made in the USA. 33-0012 \$ 59.95

#2 SWAGE-IT TOOL

For nicropress oval sleeves in sizes 1/16", 3/32" and 1/8". Swaging pressure is applied by using a wrench to tighten bolts. Cadmium plated. 1/2" x 1" x 7". 33-0002 \$ 26.00

HEAVY DUTY HAND SWAGER

Features nonslip grip. Grooves accommodate oval sleeves sizes 1/16", 3/32", 1/8", 5/32" and 3/16". Includes calibrator. 19" long. 33-0005 \$ 149.00



SNAP-ON WIRE COVERS

White, split, snap-on plastic tubes give the appearance of coated wire. The material is tough and slippery and causes no wear on sails. Dirt wipes off with a damp rag to keep sails clean and looking new. Non-yellowing. Each length is 6'. 3/32": Trapeze wires.
1/8": H-14/16 rigging (stock).
5/32": H-18/20/21, Nacra & Prindle rigging.
53-1003 3/32" Each \$ 1.75
53-1004 1/8" Each \$ 2.00
53-1005 5/32" Each \$ 2.25

1X19 STAINLESS WIRE

The strongest, least flexible wire construction. Used primarily for standing rigging and trapeze wire. Available with white or black PVC coating extruded onto the cable to protect sails from wear. Sold per foot.

02-0031	3/32" Bare	\$.45
02-0031W	3/32" White	\$.60
02-0031B	3/32" Black	\$.60
02-0041	1/8" Bare	\$.70
02-0041W	1/8" White	\$.90
02-0041B	1/8" Black	\$.90
02-0051	5/32" Bare	\$ 1.10
02-0051W	5/32" White	\$ 1.60
02-0051B	5/32" Black	\$ 1.80

7X7 STAINLESS BARE WIRE

Use: Main halyards and lanyards. Semi-flexible. Optimal turning radius is 72 times diameter. Sold per foot.

02-0022	1/16"	\$.50
02-0032	3/32"	\$.90


7X19 STAINLESS BARE WIRE

Use: Running rigging and halyards. Flexible. It resists crushing and has good resistance to wear caused by flexing. Optimal turning radius is 27 times diameter. Sold per foot.

02-0033	3/32"	\$.95
02-0043	1/8"	\$ 1.20
02-0053	5/32"	\$ 1.80

RIGGING TAPE

Protects against chafing and sharp edges while providing safety for sails, lines and rope ends. This self-bonding tape is waterproof and leaves no sticky residue. 1" x 15'. 10-3460 \$ 20.50



SHROUD ADJUSTER COVERS

Vinyl covers protect the crew and can prevent de-masting by protecting the split rings. Pair.

01-1071	8" White	\$ 9.00
01-1072	8" Black	\$ 9.00
07-3261	12" Black	\$ 8.95

M-O. SHROUD ANCHOR COMPONENTS

Stainless adjusters have 1/4" holes.

M. 25-3310	7-Hole Shroud Adjuster	\$ 10.00
N. 25-3300	10-Hole Shroud Adjuster	\$ 12.00
O. 25-3320	Twist Toggle for Hobie®/Prindle	\$ 9.60
50-20100000	Shroud Anchor Pin H-16/17/18-1/4 x 5/8	\$ 26.25
56-1012	Shroud Pin P-15/16/18-5/16 x 1.2	\$ 14.00
56-1014	Shroud Anchor Bar P-15/16/18	\$ 19.50

SHROUD TENSIONER/DE-TENSIONER

Reduce setup and take-down time on catamarans with high tension rigs. Racing class legal. Note: Shroud must be shortened 8.25". Each. 02-1060 \$ 73.50



PRO RIG TENSION GAUGE

The Pro Model gauge is designed to provide an accurate measurement of the tension in 3/32", 1/8" and 5/32" rigging wire with accurate and repeatable tuning. For standing rigging. 33-1795 \$ 112.99



HARKEN ELECTRONIC RIGTUNE PRO

Tune with precision for the winning edge! Eliminating guesswork, the fully calibrated RigTune Pro shows accurate measurements on an easy-to-read digital display. Stainless steel wire guides and cam resist deformation for accurate measurements every time. The splash-proof body of the Harken RigTune Pro allows sailors to readjust their rigs on the water. Accurate to the nearest kg on 2.5 to 5mm rigging (wire rope, rod and PBO). 28-7850 \$ 350.00

